

monitoring at said first location telecommunications traffic traversing ISDN B channels associated with said ISDN D channel to derive second monitoring data; and  
correlating said first and second monitoring data by selecting some of said second monitoring data in accordance with said first monitoring data, and taking a predetermined action in accordance with said selected second monitoring data.

2. (Amended) A method according to claim 1, including the steps of:  
monitoring additional signalling messages on a signalling link in a telecommunications network coupled to said ISDN link, to derive third monitoring data; and  
correlating said third monitoring data with at least one of said first and second monitoring data.

3. (Amended) A method according to claim 1, including the steps of:  
monitoring at a second location subscriber signalling messages on an ISDN D channel to derive additional monitoring data;  
monitoring at said second location telecommunications traffic traversing ISDN B channels associated with said ISDN D channel to derive further monitoring data; and  
correlating said additional and further monitoring data with said first and second monitoring data.

4. (Amended) A method of monitoring an ISDN link, comprising the steps of:  
monitoring subscriber signalling messages on an ISDN D channel to derive first monitoring data;  
monitoring additional signalling messages on a signalling link in a telecommunications network coupled to said ISDN link, to derive second monitoring data; and  
correlating said first and second monitoring data.

5. (Amended) An apparatus for monitoring an ISDN link, comprising:  
first equipment at a first location for monitoring subscriber signalling messages on an ISDN D channel to derive first monitoring data;  
second equipment at said first location for monitoring telecommunications traffic traversing ISDN B channels associated with said ISDN D channel to derive second monitoring data; and  
correlation apparatus coupled to said first and second equipment to receive and correlate said first and second monitoring data by selecting some of said second monitoring data in accordance with said first monitoring data, and taking a predetermined action in accordance with said selected second monitoring data.

6. (Amended) An apparatus for monitoring an ISDN link, comprising:  
first equipment for monitoring subscriber signalling messages on an ISDN D channel to derive first monitoring data;  
second equipment for monitoring additional signalling messages on a signalling link in a telecommunications network coupled to said ISDN link, to derive second monitoring data; and  
correlation apparatus coupled to said first and second equipment to receive and correlate said first and second monitoring data.

7. (Amended) A method of monitoring a telecommunications system having transmission channels and an associated signalling channel, comprising the steps of:  
monitoring at a first location signalling messages on the signalling channel to derive first monitoring data;  
selecting a transmission channel identified by reference to information contained in said first monitoring data;  
monitoring at said first location telecommunications traffic traversing the selected transmission channel to derive second monitoring data; and

*CONT*  
*B<sup>1</sup>*  
extracting information that is traversing the selected transmission channel by reference to information contained in said second monitoring data.

---

Please add the following claims, newly numbered as claims 22 – 34.

---

22. (New) The method of claim 1, wherein said predetermined action comprises providing an update in real time of summary information regarding operation of said ISDN link.

23. (New) The method of claim 1, wherein said predetermined action comprises analysing said selected second monitoring data to identify a type of service being carried on the ISDN B channel from which said selected second monitoring data are derived.

*B<sup>2</sup>*  
24. (New) The method of claim 23, wherein a spectrum of said selected second monitoring data is analysed to identify whether said type of service is a voice call, a fax call or a data call.

25. (New) The method of claim 2, wherein said signalling link is an SS7 signalling link, and said additional signalling messages are SS7 protocol messages.

26. (New) The method of claim 4, wherein said signalling link is an SS7 signalling link, and said additional signalling messages are SS7 protocol messages.

27. (New) The apparatus of claim 5, wherein said predetermined action comprises providing an update in real time of summary information regarding operation of said ISDN link.

28. (New) The apparatus of claim 5, wherein said predetermined action comprises analysing said selected second monitoring data to identify a type of service being carried on the ISDN B channel from which said selected second monitoring data are derived..

29. (New) The apparatus of claim 28, wherein a spectrum of said selected second monitoring data is analysed to identify whether said type of service is a voice call, a fax call or a data call.

30. (New) The apparatus of claim 6, wherein said signalling link is an SS7 signalling link, and said additional signalling messages are SS7 protocol messages.

31. (New) The method of claim 1, wherein said first monitoring data are derived from a plurality of D channels.

32. (New) The method of claim 7, wherein said transmission and signalling channels are carried on an Asynchronous Transfer Mode system.

33. (New) A method of assembling service detail records for transactions carried over an ISDN link, comprising the steps of:

- monitoring subscriber signalling messages on an ISDN D channel in an ISDN link;
- selecting D channel signalling messages relating to a transaction carried over said ISDN link in accordance with a predetermined criterion; and
- assembling a service detail record for said transaction from said selected D channel signalling messages.

34. (New) An apparatus for assembling service detail records for transactions carried over an ISDN link, comprising:

- means for monitoring subscriber signalling messages on an ISDN D channel in an ISDN link;
- means for selecting D channel signalling messages relating to a transaction carried over said ISDN link in accordance with a predetermined criterion; and
- means for assembling a service detail record for said transaction from said selected D channel signalling messages.

---